

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product Name: Nobiltone 20-Minute Heat-Cure
Liquid
Product Number: 7496-7498
Chemical Name: Acrylic Liquid (monomer)
Chemical Family: Methyl Methacrylate

Company Identification

Nobilium Co., Div. of CMP Industries LLC
413 North Pearl St
Albany, NY 12207-1311 USA
(518)-434-3147 (For product information)
(800)-424-9300 (For emergencies)

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Amount</u>	<u>CAS Number</u>
METHYL METHACRYLATE	> 80.0 %	80-62-6
ETHYLENE GLYCOL DIMETHACRYLATE	< 20.0 %	97-90-5
DIMETHYL P TOLUIDINE	< 2.0 %	99-97-8
2-BENZOYL-5-METHOXYPHENOL	< 2.0 %	131-57-7

(See Section 8 for exposure guidelines)

(See Section 15 for regulatory information)

HAZARDS DISCLOSURE

This product contains hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

3. HAZARDS IDENTIFICATION

***** EMERGENCY OVERVIEW *****
*
* Prolonged exposure can lead to kidney and liver *



* damage. *
* *

POTENTIAL HEALTH EFFECTS

EYE:

Can cause slight eye irritation.

SKIN:

Can cause moderate skin irritation and sensitization.

INHALATION:

can cause respiratory irritation. Prolonged exposure can lead to headaches, nausea, drowsiness and unconsciousness.

INGESTION:

Ingestion is not considered a potential route of exposure. Harmful if swallowed.

SIGNS AND SYMPTOMS OF EXPOSURE:

Headaches, nausea, staggering gait, confusion, drowsiness and unconsciousness.

CHRONIC EFFECTS:

Prolonged and repeated exposure can cause the following: allergic skin reaction, kidney and liver damage.

REPRODUCTIVE HAZARDS:

None.

CARCINOGENICITY INFORMATION:

No known cancer hazards.

TARGET ORGAN:

Nose, Liver, Kidneys & Eyes.

MEDICAL CONDITIONS AGRAVATED BY EXPOSURE:

Individuals with pre-existing skin disorders may be more susceptible to severe irritation and possible sensitization.

4. FIRST AID MEASURES

EYE CONTACT FIRST AID:

Flush eyes with water for 15 minutes, including under eyelids. Contact a physician.



(section 4 continued)

SKIN CONTACT FIRST AID:

Remove contaminated clothing. Wash skin with soap and water. Contact a physician.

INHALATION FIRST AID:

Remove to fresh air. If breathing is difficult, give oxygen. Get medical help if discomfort persists.

INGESTION FIRST AID:

Do not induce vomiting. Dilute with 2 glasses of water. Never give anything to an unconscious person. Contact a physician.

STATEMENT OF PRACTICAL TREATMENT:

Maintain airway. Provide oxygen and/or ventilation assistance, if needed. Treat burns or allergic reactions conventionally after decontamination.

MISCELLANEOUS:

Wash clothing thoroughly before reuse.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

TCC Flash Point: 10 C (50.0 F)
Autoignition Temperature: 2.1 C (35.8 F)

FLAMMABLE LIMITS IN AIR

LEL: 2.1 %
UEL: 12.0 %

FLAMMABLE PROPERTIES:

Vapors may travel to source of ignition and flash back. Heat can cause polymerization. Heated containers will explode.

EXTINGUISHING MEDIA:

Carbon dioxide, chemical foam, or dry chemical.

FIRE & EXPLOSION HAZARDS:

Spontaneous polymerization may occur on prolonged storage.

FIRE FIGHTING INSTRUCTIONS:

Wear self-contained breathing apparatus and full protective gear. Use water spray to cool containers.

EXPLOSION HAZARD - fight fire from protected location.

COMBUSTION PRODUCTS:

Not known.



6. ACCIDENTAL RELEASE MEASURES

SAFEGUARDS (PERSONNEL):

Eliminate all sources of ignition - heat, sparks, flame, electricity, impact and friction. Evacuate area. Wear appropriate personal protective equipment.

LARGE SPILLS PROCEDURE:

Absorb spill with inert material (e g, dry sand or earth), then transfer to proper containers for disposal, use non-sparkling tools. Contaminated monomer may be unstable, add inhibitor to prevent polymerization.

CAUTION: Keep spills and cleaning runoffs out of sewers and open bodies of water. Spills on porous surfaces can contaminate the groundwater.

7. HANDLING AND STORAGE

HANDLING (PERSONNEL):

Wash face and hands thoroughly with soap and water after handling and before eating, drinking or smoking.

HANDLING (PHYSICAL ASPECTS):

Store in cool dry place away from heat, sparks, flame and direct sunlight. Close container after each use. Ground all metal containers when transferring. Use explosion-proof equipment. Check inhibitor levels every three(3) months.

STORAGE PRECAUTIONS:

Store in a cool dry place away from heat, sparks, flame and direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

EYE / FACE PROTECTION REQUIREMENTS:

Wear safety glasses or chemical splash goggles.

SKIN PROTECTION REQUIREMENTS:

Impervious clothing.

RESPIRATORY PROTECTION REQUIREMENTS:

Do not breathe mists or vapors. Use self-contained breathing apparatus when needed or when level exceeds 100 ppm.



(section 8 continued)

MISCELLANEOUS:

Local exhaust ventilation is preferred since it prevents contamination dispersion into the work area by controlling it at its source.

EXPOSURE GUIDELINES:

METHYL METHACRYLATE

OSHA PEL: 100 ppm, 410 mg/m³

OSHA TWA: 100 ppm, 410 mg/m³

DIMETHYL P TOLUIDINE

OSHA PEL: 10 mg/m³

OSHA TWA: 2.5 mg/m³

HYDROQUINONE

OSHA PEL: 2 mg/m³

OSHA TWA: 2 mg/m³

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Liquid
COLOR: Clear
ODOR: Fruity
BOILING POINT: 101°C, 214°F F
VAPOR PRESSURE: 29 mm Hg @ 68 F
VAPOR DENSITY: 3.5 @ 60°F (Air = 1)
SOLUBILITY IN WATER ...: Moderate 1.6 gm/100 gms @ 20°C, 214°F
SPECIFIC GRAVITY: 0.94 (Water = 1)

10. STABILITY AND REACTIVITY

STABILITY:

Stable.

POLYMERIZATION:

Hazardous polymerization will occur.

INCOMPATIBILITY WITH OTHER MATERIALS:

Reducing agents, oxidizing agents and UV light. Material has strong solvent properties and can soften paint and rubber.

DECOMPOSITION:

Oxides of carbon when burned.

CONDITIONS TO AVOID:

Heat above 70°F, 21°C, and source of ignition, aging and contamination, peroxides, acids, alkalies and amines.



11. TOXICOLOGICAL INFORMATION

METHYL METHACRYLATE

Test Code: TCLO
Species: Human
Results: 125 ppm

Test Code: LC50
Species: Rat
Results: 3750 ppm

DIMETHYL P TOLUIDINE

Test Code: LC50
Species: Rat
Results: 149 ppm/7 hr

Test Code: Oral LD50
Species: Rat
Results: 467 mg/kg

Test Code: Oral LD50
Species: Mouse
Results: 250 mg/kg

12. ECOLOGICAL INFORMATION

No information available.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

14. TRANSPORTATION INFORMATION



PRODUCT LABEL: Nobiltone 20-Minute Heat-Cure Liquid
D.O.T. SHIPPING NAME: Methyl Methacrylate, Inhibited
TECHNICAL SHIPPING NAME ...: N/A
D.O.T. HAZARD CLASS: Flammable Liquid
UN NUMBER: N/A



15. REGULATORY INFORMATION

EEC Symbols and Indications of Danger:

Harmful (Xn), Irritant (Xi)



R-Phrases:

R10 - Flammable.

R20/21/22 - Harmful by inhalation, in contact with skin, and if swallowed.

R36/37/38 - Irritating to eyes, respiratory system, and skin.

R42/43 - May cause sensitization by inhalation and skin contact.

R48 - Danger of serious damage to health by prolonged exposure.

S-Phrases:


S16 - Keep away from sources of ignition. No smoking.

S3 - Keep in a cool place.

S8 - Keep container dry.

WHMIS Hazard Symbols:

Class B - Flammable and Combustible Material, Class D2 - Materials
Causing Other Toxic Effects



Canadian Disclosure List

METHYL METHACRYLATE (80-62-6)

SARA Title III - Section 313

METHYL METHACRYLATE (80-62-6)

CERCLA Hazardous Substances

METHYL METHACRYLATE (80-62-6) -- RQ 1000 lb

RCRA Hazardous Substances

METHYL METHACRYLATE (80-62-6) -- RCRA Code: U162

Title V

METHYL METHACRYLATE (80-62-6)

SC Toxic Air Pollutants List

METHYL METHACRYLATE (80-62-6)



16. OTHER INFORMATION

PREPARED BY: Shirley A. McCoy
APPROVED BY: Abdul Khan
TITLE: Q. C. Manager
APPROVAL DATE: April 17, 2003
SUPERCEDES DATE ...: June 10, 1998
MSDS NUMBER: 7496-7498
RTN NUMBER: 00000259 (Official Copy)

This information is furnished without warranty, expressed or implied,
except that it is accurate to the best knowledge of CMP Industries Inc.
The data on this sheet are related only to the specific material
designated herein. CMP Industries Inc assumes no legal responsibility
for use or reliance upon these data.

END OF MSDS

